

TPO Spray Adhesive



EverGuard® TPO QuickSpray Adhesive



Description:

EverGuard® TPO Quick Spray Adhesive is a sprayable, solvent-based contact adhesive useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

Features and Benefits:

- Faster installation than traditional bonding adhesive
- High initial tack
- Available in sustainable, reusable canisters
- Shelf life-2 years from the date of manufacture

Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- For TPO membrane, spraying from 8"– 12" (203 mm–305 mm) away, apply adhesive uniformly to both the substrate and the membrane underside
- As primer for SA Vapor Retarder, apply to the substrate only
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply at an ambient temperature of 20°F (-6.7°C) and above. The cylinders must be kept above 50°F (10°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C).
- Apply pressure with a push broom or weighted roller to ensure complete bonding
- To clean Hose & Gun Kit, attach hose and gun to EverGuard® Quick Spray or EverGuard® Quick Spray LV50 Cleaning Kit and run cleaner through hose and gun for approximately 10 – 15 seconds. Each cleaner canister should get approximately 9 – 10 cleanings for the 10 square size.
- To arrange for empty large canister returns, call 877-423-7663

Product Details:

EverGuard® TPO Quick Spray Adhesive

- SKU 7806 – 3 squares - 13.65 lb. (6.2 kg)
- SKU 7792 – 10 squares - 40.15 lb. (18.2 kg)
- SKU 7830 – 18 squares - 87 lb. (39.5 kg)
- SKU 7808 – 49 squares - 209.6 lb. (95.1kg)
- SKU 7810 – 105 squares - 448 lb. (203.2 kg)
- Canister Coverage Rate: 40 lb. (18.14 kg) - 10 sq. (93 sq. meters); 9 lb. (4.08 kg) - 3 sq. (27.87 sq. meters)
- VOC: 489 g/L
- Shelf Life: 1 year
- Installation Temperature: 20°F (-6.7°C) and rising
- Cleaner SKU: 7802
- Hose & Gun SKU: 7804 or 7805
- Hose Splitter: 7826
- 25' Hose: 7825

Coverage rates and flash time may vary in colder temperatures.

Codes & Standards:

- **UL Classified:** Refer to UL Online Certification Directory for actual assemblies.



- **State of Florida Approved**



For additional information, contact GAF Technical Support at 1-800-766-3411 or technicalquestions@gaf.com



Visit gaf.com/QuickSpray

We protect what matters most™