

EverGuard® TPO
GAF **Primer**



Description:

EverGuard® TPO Primer and EverGuard® TPO Low VOC Primer help prepare metal and membrane for application of cover tape, and help prepare membrane and pourable sealer pockets to apply EverGuard® One-Part or Two-Part Pourable Sealant.

Application:

Cover Tape

When installing cover tape, apply the primer with a 3" roller to both the metal and membrane. Allow primer to flash off before applying tape.

HW Cover Tape

When installing Heat Weld Cover tape, apply the primer with a 3" roller to the metal only. Allow the primer to flash off before applying heat weld cover tape.

Pourable Sealant Pocket

Prior to filling the TPO Pourable Sealant Pocket, you must prime the inside vertical pan sides. Fill the base of the pans with non-shrink grout and top with a minimum 2" thickness of GAF One-Part or Two-Part Pourable Sealant.

SPECIFICATIONS	TPO Primer	Low VOC TPO Primer
Can size	1 gallon	1 gallon
Cans per carton	6	6
Coverage Rates	200-250 sq. ft. per gallon (18.6-23.2 m ² per liter)	200-225 sq. ft. per gallon (18.6-20.9 m ² per liter)
Product SKUs	755B	755D



Visit [gaf.com](https://www.gaf.com)

For additional information, contact GAF Technical Support at **1-800-766-3411** or technicalquestions@gaf.com

We protect what matters most™

